

Worden Safety Products Catalog *September 2003*

Scroll to view entire Rail Road Chock selection or click on category below to go right to it.

RR Wheel Chocks



- **Single Rail Chocks**
- **Double Rail Chocks**

Call For pricing:

**(800)-4-CHOCKS
(800) . 424 . 6257**

**email: sales@chocks.com
info@chocks.com**

SRC - Single Rail Chock

The SRC Single Rail Road chock is the safety workhorse of the industry. This chock is designed to hold a Rail Road car in one direction only.

Replaceable spur makes this chock a great value.

- **MATERIAL:** Heat Treated Steel
- **SIZE:** 3.75"H x 4"W x 7.5"L
- **WEIGHT:** 8 lbs.



MATERIAL SAFETY DATA SHEET

MEETS OSHA REGS. 1910.110(15), 1901.111 (13) 1910.30 (A) (5)

RAIL TYPE

Exposed Rail

FEATURES

Reliable, replaceable heat treated steel spurs keep chocks from slipping on the rails and increase the life of the chock.

SFC - Single Flagged Chock

The SFC Single RR chock is one of the safety workhorses of the industry. This chock is designed to hold a RR car in one directions.

The dimensions of the hi-vis Sign are 9 1/2"H x 7 1/2"W

Heavy Duty 30" chain.

- MATERIAL: Heat Treated Steel
- SIZE: 3.75"H x 4"W x 7.5"L
- WEIGHT: 16 lbs.



MATERIAL SAFETY DATA SHEET

Meets OSHA Regs. 1910.110(15), 1901.111 (13) 1910.30 (A) (5)

Rail Type

Exposed Rail

Features

Reliable, replaceable heat treated steel spurs keep chocks from slipping on the rails and increase the life of the chock.

DRC - Dual Rail Chock

The DRC Double RR chock is one of the safety workhorses of the industry. This chock is designed to hold a RR car in both directions.

Heavy Duty 26" chain.

Replaceable spur makes this chock a great value.

- MATERIAL: Heat Treated Steel
- SIZE: 3.75"H x 4"W x 7.5"L
- WEIGHT: 16 lbs.



MATERIAL SAFETY DATA SHEET

Meets OSHA Regs. 1910.110(15), 1901.111 (13) 1910.30 (A) (5)

Rail Type

Exposed Rail

Features

Reliable, replaceable heat treated steel spurs keep chocks from slipping on the rails and increase the life of the chock.
26" chain
11.5" handle

DFC - Dual Flagged Rail Chock

The DFC Dual Flagged RR chock gives safety workers the safety of a double chock with the visibility of a hi-vis flag to let co-workers know that the cars wheel is chocked. This chock is designed to hold a RR car in both directions.

The dimensions of the hi-vis Sign are 9 1/2"H x 7 1/2"W

Heavy Duty 26" chain.

Replaceable spur makes this chock a great value.

- MATERIAL: Heat Treated Steel
- SIZE: 3.75"H x 4"W x 7.5"L
- WEIGHT: 16 lbs.



MATERIAL SAFETY DATA SHEET

MEETS OSHA REGS. 1910.110(15), 1901.111 (13) 1910.30 (A) (5)

RAIL TYPE

Exposed Rail

FEATURES

Reliable, replaceable heat treated steel spurs keep chocks from slipping on the rails and increase the life of the chock.
26" chain
11.5" handle